

View Online at <https://aerobasegroup.com/nsn/5962-00-311-3678>

Body Length:

Between 1.200 inches and 1.290 inches

Body Width:

Between 0.515 inches and 0.580 inches

Body Height:

Between 0.050 inches and 0.230 inches

Maximum Power Dissipation Rating:

270.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and positive outputs and w/decoded output and w/strobe and w/totem pole output

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

6 input

Design Function And Quantity:

1 decoder, four to sixteen line

Case Outline Source And Designator:

-0-015-aa joint electron device engineering council

Time Rating Per Characteristic:

36.00 nanoseconds propagation delay time, low to high level output and 33.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0