NSN 5962-00-311-3678

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-311-3678

The state of the s
Body Length:
Between 1.200 inches and 1.290 inches
Body Width:
Between 0.515 inches and 0.580 inches
Body Height:
Between 0.050 inches and 0.230 inches
Maximum Power Dissipation Rating:
270.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and w/decoded output and w/strobe and w/totem pole output
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
6 input
Design Function And Quantity:
1 decoder, four to sixteen line
Case Outline Source And Designator:
-0-015-aa joint electron device engineering council
Time Rating Per Chacteristic:
36.00 nanoseconds propagation delay time, low to high level output and 33.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiia:

riig:

A458a0