## NSN 5962-00-318-3136

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-318-3136

| Body Length:  |
|---|
| Between 0.660 inches and 0.785 inches   |
| Body Width:   |
| Between 0.220 inches and 0.280 inches   |
| Body Height:  |
| Between 0.140 inches and 0.180 inches   |
| Maximum Power Dissipation Rating:   |
| 750.0 milliwatts  |
| Operating Tempurature Range:  |
| -55.0/+125.0 degrees celsius  |
| Storage Tempurature Range:  |
| -65.0/+150.0 degrees celsius  |
| Features Provided:  |
| Hermetically sealed and monolithic and positive outputs   |
| Inclosure Material:   |
| Ceramic   |
| Inclosure Configuration:  |
| Dual-in-line  |
| Input Circuit Pattern:  |
| 2 input   |
| Case Outline Source And Designator:   |
| T0-116 joint electron device engineering council  |
| Terminal Surface Treatment:   |
| Gold  |
| Voltage Rating And Type Per Characteristic:   |
| 15.0 volts power source   |
| Precious Material And Location:   |
| Terminals gold  |
| Precious Material:  |
| Gold  |
| Test Data Document:   |
| 49956-570671 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                           |
| Terminal Type And Quantity:   |
| 14 printed circuit  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| Yes - demil/mli   |

**Fiig:** A458a0