NSN 5962-00-323-1084

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/psp/5062-00-323-1084

View Online at https://aerobasegroup.com/nsn/5962-00-323-1084
Body Length:
Between 0.725 inches and 0.825 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
0.205 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and negative outputs and high speed
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line Dual-in-line
Input Circuit Pattern:
6 input
Design Function And Quantity:
1 comparator, voltage
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
15.0 volts power source
Time Rating Per Chacteristic:
150.00 nanoseconds propagation delay time, low to high level output and 150.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
49956-570795 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig:

A458a0

Yes - demil/mli