# NSN 5962-00-324-1392

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-324-1392

# **Body Length:**

Between 0.330 inches and 0.350 inches

### **Body Width:**

Between 0.240 inches and 0.260 inches

# **Body Height:**

Between 0.030 inches and 0.070 inches

# **Maximum Power Dissipation Rating:**

112.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs

#### **Inclosure Material:**

# Ceramic and glass

Inclosure Configuration:

Flat pack

#### **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

Quad 2 input

#### **Design Function And Quantity:**

4 gate, nand

#### Case Outline Source And Designator:

T0-88 joint electron device engineering council

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

#### Time Rating Per Chacteristic:

37.00 nanoseconds propagation delay time, low to high level output and 37.00 nanoseconds propagation delay time, high to low level

output

#### **Special Features:**

Formed leads

#### **Terminal Type And Quantity:**

14 flat leads

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

Yes - demil/mli

# **NSN 5962-00-324-1392** Digital Microcircuit - Page 2 of 2

Fiig: A458a0

