NSN 5962-00-324-3023

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-324-3023 **Body Length:** 1.310 inches **Body Width:** 0.500 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 170.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and positive outputs and medium speed and w/decoded output and w/totem pole output and w/strobe **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 6 input **Design Function And Quantity:** 1 decoder, four to sixteen line **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source **Time Rating Per Chacteristic:** 36.00 nanoseconds propagation delay time, low to high level output and 33.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 73030-5e8071/61 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 24 printed circuit Shelf Life: N/a Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0