NSN 5962-00-329-4633

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-329-4633
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
60.0 milliwatts
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and positive outputs and high speed
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Hex 1 input
Criticality Code Justification:
Feat
Design Function And Quantity:
6 inverter, digital
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
22.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level
output
Special Features:
Item must comply with rqmt of desc production standard no. L01470; for navy nuclear propulsion plant products only

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

NSN 5962-00-329-4633

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0