# NSN 5962-00-329-4685

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-329-4685

Bodv	l er	nath:
Douv	LCI	ıuıı.

Between 0.660 inches and 0.785 inches

**Body Width:** 

Between 0.220 inches and 0.280 inches

**Body Height:** 

Between 0.140 inches and 0.180 inches

#### **Operating Tempurature Range:**

+0.0/+70.0 degrees celsius

#### **Storage Tempurature Range:**

-65.0/+150.0 degrees celsius

#### **End Application:**

Wsd: missile, all-weather anti-ship, harpoon (agm-84)

#### **Features Provided:**

Monolithic and positive outputs and edge triggered and w/clear and presettable and w/enable

#### **Inclosure Material:**

Plastic

# **Inclosure Configuration:**

Dual-in-line

# **Output Logic Form:**

Transistor-transistor logic

# **Input Circuit Pattern:**

Dual 4 input

# **Criticality Code Justification:**

Feat

# **Design Function And Quantity:**

2 flip-flop, clocked and 2 flip-flop, d-type

# **Case Outline Source And Designator:**

T0-116 joint electron device engineering council

#### **Terminal Surface Treatment:**

Solder

# **Voltage Rating And Type Per Characteristic:**

-1.5 volts power source and 5.5 volts power source

# **Time Rating Per Chacteristic:**

25.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level output

#### **Special Features:**

Weapon system essential

# **Terminal Type And Quantity:**

14 printed circuit

# Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5962-00-329-4685

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0