

View Online at <https://aerobasegroup.com/nsn/5962-00-329-4691>

**Body Length:**

Between 0.660 inches and 0.785 inches

**Body Width:**

Between 0.220 inches and 0.280 inches

**Body Height:**

Between 0.140 inches and 0.180 inches

**Maximum Power Dissipation Rating:**

140.0 milliwatts

**Operating Temperature Range:**

+0.0/+75.0 degrees celsius

**Storage Temperature Range:**

-55.0/+125.0 degrees celsius

**Features Provided:**

Monolithic and negative outputs and high speed and high gain and adjustable

**Inclosure Material:**

Plastic

**Inclosure Configuration:**

Dual-in-line

**Criticality Code Justification:**

Feat

**Design Function And Quantity:**

3 amplifier, differential and 2 schmitt trigger

**Case Outline Source And Designator:**

T0-116 joint electron device engineering council

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-10.0 volts power source and 0.0 volts power source

**Time Rating Per Characteristic:**

8.50 nanoseconds propagation delay time, low to high level output and 7.50 nanoseconds propagation delay time, high to low level output

**Special Features:**

Item must comply with rqmt of @desc production standard no. L01477; for navy nuclear propulsion plant products only

**Terminal Type And Quantity:**

14 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0