# NSN 5962-00-329-8411

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-329-8411

# **Body Length:**

Between 0.370 inches and 0.395 inches

# Body Width:

Between 0.240 inches and 0.260 inches

## **Body Height:**

Between 0.050 inches and 0.085 inches

# **Maximum Power Dissipation Rating:**

500.0 milliwatts

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **Features Provided:**

Hermetically sealed and monolithic and positive outputs and w/enable and expandable and w/buffered output and wire-or outputs and bipolar

and programmable and programmed and w/decoded output

#### **Inclosure Material:**

Ceramic and glass

# Inclosure Configuration:

Flat pack

## **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

8 input

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

## **Time Rating Per Chacteristic:**

25.00 nanoseconds propagation delay time, low to high level output and 75.00 nanoseconds propagation delay time, low to high level output

## Memory Device Type:

Rom

#### **Memory Capacity:**

Unknown

#### Test Data Document:

82577-932085 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### **Terminal Type And Quantity:**

24 flat leads

## Shelf Life:

N/a

## Unit Of Measure:

--

# Demilitarization:

# NSN 5962-00-329-8411

Memory Microcircuit - Page 2 of 2

**Fiig:** A458a0

