## NSN 5962-00-331-4372

Linear Microcircuit - Page 1 of 1



| view Online at https://aerobasegroup.com/hsh/5962-00-551-4572                |
|--|
| Body Outside Diameter:   |
| Between 0.335 inches and 0.370 inches  |
| Body Height:   |
| Between 0.165 inches and 0.185 inches  |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| Features Provided:   |
| Hermetically sealed and monolithic and negative outputs and positive outputs |
| Inclosure Material:  |
| Ceramic and glass  |
| Inclosure Configuration:   |
| Can  |
| Input Circuit Pattern:   |
| 6 input  |
| Design Function And Quantity:  |
| 1 amplifier, differential and 1 amplifier, video                             |
| Case Outline Source And Designator:  |
| T0-100 joint electron device engineering council                             |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:                                  |
| 6.0 volts power source   |
| Terminal Type And Quantity:  |
| 10 pin   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A458a0   |