

View Online at <https://aerobasegroup.com/nsn/5962-00-331-9230>

Body Length:

Between 0.755 inches and 0.785 inches

Body Width:

0.280 inches

Body Height:

Between 0.130 inches and 0.180 inches

Maximum Power Dissipation Rating:

76.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and hermetically sealed and positive outputs and w/enable and edge triggered and w/clear and w/buffered output and complementary outputs

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

6 input

Design Function And Quantity:

4 flip-flop, clocked and 4 flip-flop, d-type

Time Rating Per Characteristic:

30.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

73030-5e8071/94 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0