## NSN 5962-00-333-8806

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-333-8806

#### **Body Length:**

Between 0.250 inches and 0.260 inches

## Body Width:

Between 0.140 inches and 0.150 inches

## **Body Height:**

Between 0.035 inches and 0.050 inches

### **Maximum Power Dissipation Rating:**

140.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and high speed and medium power

#### **Inclosure Material:**

Glass and metal

## Inclosure Configuration:

Flat pack

## **Output Logic Form:**

Transistor-transistor logic

### Input Circuit Pattern:

4 wide 2-2-2-3 input

#### **Design Function And Quantity:**

1 gate, and-or invert

#### **Case Outline Source And Designator:**

T0-84 joint electron device engineering council

#### **Terminal Surface Treatment:**

Gold

#### Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

#### **Precious Material And Location:**

Body and terminal surfaces gold

#### **Precious Material:**

Gold

#### Test Data Document:

03640-6088472 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### **Terminal Type And Quantity:**

14 flat leads

#### Shelf Life:

N/a

## Unit Of Measure:

# NSN 5962-00-333-8806

Digital Microcircuit - Page 2 of 2

Demilitarization:

No

Fiig:

A458a0

