# NSN 5962-00-333-8974

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-333-8974

## **Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

## **Body Height:**

Between 0.165 inches and 0.185 inches

## Maximum Power Dissipation Rating:

300.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Monolithic and hermetically sealed and negative outputs and positive outputs and adjustable

#### **Inclosure Material:**

Glass and metal

Inclosure Configuration:

## Can

Input Circuit Pattern:

2 input

## **Design Function And Quantity:**

1 amplifier, operational, general purpose

## Case Outline Source And Designator:

T0-99 joint electron device engineering council

## **Terminal Surface Treatment:**

Tin

## **Time Rating Per Chacteristic:**

60.00 nanoseconds propagation delay time, low to high level output

#### **Test Data Document:**

12464-b77t0146 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### **Demilitarization:**

No

## Fiig:

A458a0