NSN 5962-00-333-9336



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-00-333-9336 **Body Length:** Between 0.371 inches and 0.409 inches **Body Width:** Between 0.240 inches and 0.290 inches **Body Height:** Between 0.030 inches and 0.070 inches **Maximum Power Dissipation Rating:** 550.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and positive outputs and high speed and asynchronous and complementary outputs and resettable and synchronous and w/enable **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 9 input **Design Function And Quantity:** 1 shift register, universal **Terminal Surface Treatment:** Gold Voltage Rating And Type Per Characteristic: -0.5 volts power source and 5.5 volts power source **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold **Test Data Document:** 82577-932064 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 flat leads

Demilitarization:

Unit Of Measure:

Yes - demil/mli

Shelf Life:

N/a

NSN 5962-00-333-9336Digital Microcircuit - Page 2 of 2



Fiig:

A458a0