

View Online at <https://aerobasegroup.com/nsn/5962-00-341-3096>

**Body Length:**

Between 0.740 inches and 0.830 inches

**Body Width:**

Between 0.275 inches and 0.310 inches

**Body Height:**

Between 0.050 inches and 0.180 inches

**Maximum Power Dissipation Rating:**

900.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and negative outputs and positive outputs and high speed

**Inclosure Material:**

Ceramic and metal

**Inclosure Configuration:**

Dual-in-line

**Input Circuit Pattern:**

Dual 1 channel

**Design Function And Quantity:**

2 driver, switch, field effect transistor and 2 switch, analog

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

15.0 volts power source

**Time Rating Per Characteristic:**

130.00 nanoseconds propagation delay time, low to high level output and 150.00 nanoseconds propagation delay time, high to low level output

**Precious Material And Location:**

Terminal surface gold

**Precious Material:**

Gold

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0