

View Online at <https://aerobasegroup.com/nsn/5962-00-341-3096>

Body Length:

Between 0.740 inches and 0.830 inches

Body Width:

Between 0.275 inches and 0.310 inches

Body Height:

Between 0.050 inches and 0.180 inches

Maximum Power Dissipation Rating:

900.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and negative outputs and positive outputs and high speed

Inclosure Material:

Ceramic and metal

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

Dual 1 channel

Design Function And Quantity:

2 driver, switch, field effect transistor and 2 switch, analog

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

15.0 volts power source

Time Rating Per Characteristic:

130.00 nanoseconds propagation delay time, low to high level output and 150.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminal surface gold

Precious Material:

Gold

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0