NSN 5962-00-344-4378

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-344-4378

Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
96.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and medium power and medium speed
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Diode-transistor logic
Input Circuit Pattern:
Hex 1 input
Design Function And Quantity:
6 inverter, digital
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Time Rating Per Chacteristic:
80.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
92685-10000c051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing

92685-10000c051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0