# NSN 5962-00-348-2773

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-348-2773

#### **Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

#### **Body Height:**

Between 0.165 inches and 0.185 inches

# Maximum Power Dissipation Rating:

600.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Monolithic and hermetically sealed and positive outputs and edge triggered and resettable and adjustable

#### **Inclosure Material:**

Glass and metal

#### Inclosure Configuration:

# Can

Input Circuit Pattern:

4 input

#### **Design Function And Quantity:**

1 timer

### Case Outline Source And Designator:

T0-99 joint electron device engineering council

# **Terminal Surface Treatment:**

Gold

#### **Time Rating Per Chacteristic:**

100.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level output

#### **Precious Material And Location:**

Terminals gold

#### **Precious Material:**

Gold

# Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0