NSN 5962-00-349-7080

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-349-7080 **Body Length:** Between 0.660 inches and 0.785 inches **Body Width:** Between 0.240 inches and 0.280 inches **Body Height:** Between 0.140 inches and 0.180 inches **Maximum Power Dissipation Rating:** 76.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and positive outputs and medium speed and w/enable and w/buffered output and edge triggered and **Inclosure Material:** Ceramic and metal **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 9 input **Design Function And Quantity:** 6 flip-flop, clocked and 6 flip-flop, d-type **Terminal Surface Treatment:** Gold Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold **Test Data Document:** 07187-4008080 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 printed circuit Shelf Life:

Demilitarization: Yes - demil/mli

Unit Of Measure:

N/a

NSN 5962-00-349-7080Digital Microcircuit - Page 2 of 2



Fiig:

A458a0