## NSN 5962-00-350-8434

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-350-8434

Body Lo	ength:
0.785 in	
Body W	
0.260 in	
Body H	
0.180 in	
	Im Power Dissipation Rating:
400.0 m	
Operati	ng Tempurature Range:
	25.0 degrees celsius
	e Tempurature Range:
	50.0 degrees celsius
Feature	s Provided:
Monolith	ic and hermetically sealed and positive outputs and externally compensated
Inclosu	re Material:
Ceramic	and glass
Inclosu	re Configuration:
Dual-in-	line
Input C	ircuit Pattern:
2 input	
Design	Function And Quantity:
1 amplif	ier, dc and 1 amplifier, wideband
Termina	al Surface Treatment:
Solder	
Voltage	Rating And Type Per Characteristic:
7.0 volts	power source
Preciou	s Material And Location:
Termina	I surface gold
Preciou	s Material:
Gold	
Test Da	ta Document:
80063-s	m-b-525290 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; ex	cludes any specification, standard or other document that may be referenced in a basic governing drawing)
Termina	al Type And Quantity:
14 printe	ed circuit
Shelf Li	fe:
N/a	
Unit Of	Measure:
Demilita	arization:
Yes - de	emil/mli
Fiig:	
A458a0	