## NSN 5962-00-350-8435

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-350-8435 **Body Length:** 0.785 inches **Body Width:** 0.260 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 400.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and positive outputs and negative outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 comparator, voltage, differential **Terminal Surface Treatment:** Gold or tin **Voltage Rating And Type Per Characteristic:** 7.0 volts power source **Time Rating Per Chacteristic:** 80.00 nanoseconds propagation delay time, low to high level output and 80.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold **Test Data Document:** 80063-sm-b-525292 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a

Yes - demil/mli

**Unit Of Measure:** 

**Demilitarization:** 

## NSN 5962-00-350-8435

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0