NSN 5962-00-353-0827

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-353-0827
Body Length:
Between 1.200 inches and 1.290 inches
Body Width:
Between 0.515 inches and 0.580 inches
Body Height:
Between 0.050 inches and 0.230 inches
Maximum Power Dissipation Rating:
640.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and w/enable and medium speed
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 5 input
Design Function And Quantity:
2 latch
Case Outline Source And Designator:
-0-015-aa joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
30.00 nanoseconds propagation delay time, low to high level output and 25.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
07148-80740 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

NSN 5962-00-353-0827Digital Microcircuit - Page 2 of 2



Fiig:

A458a0