

View Online at <https://aerobasegroup.com/nsn/5962-00-356-7673>

**Body Length:**

Between 0.660 inches and 0.785 inches

**Body Width:**

Between 0.220 inches and 0.280 inches

**Body Height:**

Between 0.140 inches and 0.180 inches

**Maximum Power Dissipation Rating:**

670.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Monolithic and hermetically sealed and high gain and positive outputs and negative outputs and high voltage

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Input Circuit Pattern:**

2 input

**Design Function And Quantity:**

1 comparator, voltage, differential

**Case Outline Source And Designator:**

T0-116 joint electron device engineering council

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

13.0 volts power source

**Time Rating Per Characteristic:**

200.00 nanoseconds propagation delay time, low to high level output

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

14 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0