NSN 5962-00-360-6516

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-360-6516

Dedutemethy
Body Length:
0.405 inches
Body Width:
0.280 inches
Body Height:
0.070 inches
Maximum Power Dissipation Rating: 650.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and negative outputs and positive outputs and w/buffered output and w/enable and w/storage
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
10 input
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
150.00 nanoseconds propagation delay time, low to high level output and 150.00 nanoseconds propagation delay time, high to low level
output
Memory Device Type:
Rom
Memory Capacity:
Unknown
Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Test Data Document:
06481-970345 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:

24 flat leads

Shelf Life:

N/a

NSN 5962-00-360-6516

Memory Microcircuit - Page 2 of 2

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

