# NSN 5962-00-369-8106

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-369-8106

## **Body Length:**

Between 0.660 inches and 0.785 inches

## Body Width:

Between 0.220 inches and 0.280 inches

# **Body Height:**

Between 0.140 inches and 0.180 inches

## Maximum Power Dissipation Rating:

6.0 watts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and high power and high voltage

#### **Inclosure Material:**

# Ceramic and glass

## Inclosure Configuration:

Dual-in-line

## Input Circuit Pattern:

7 input

### **Design Function And Quantity:**

4 driver, power and 4 driver, relay

### Case Outline Source And Designator:

T0-116 joint electron device engineering council

### **Terminal Surface Treatment:**

Solder

### Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

### **Time Rating Per Chacteristic:**

750.00 nanoseconds propagation delay time, low to high level output and 500.00 nanoseconds propagation delay time, high to low level output

### **Test Data Document:**

07148-80734 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### **Terminal Type And Quantity:**

14 printed circuit

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0