NSN 5962-00-370-1244

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-370-1244

Body Length:

Between 0.660 inches and 0.785 inches

Body Width:

Between 0.240 inches and 0.295 inches

Body Height:

Between 0.140 inches and 0.180 inches

Maximum Power Dissipation Rating:

1.3 watts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and negative outputs and positive outputs

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

6 input

Design Function And Quantity:

4 switch, ladder, digital to analog

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

20.0 volts power source

Time Rating Per Chacteristic:

500.00 nanoseconds propagation delay time, low to high level output

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Test Data Document:

07187-4008096 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-00-370-1244

Linear Microcircuit - Page 2 of 2

Fiig: A458a0

