## NSN 5962-00-370-2340

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-370-2340

Between 0.335 inches and 0.370 inches Body Height: Between 0.165 inches and 0.185 inches Maximum Power Dissipation Rating: 400.0 millivatts  Operating Tempurature Range: 28.0 /r450.0 degrees celsius Storage Tempurature Range: 65.0 /r450.0 degrees celsius Features Provided: Hermetically sealed and monolithic and high gain and fixed and positive outputs inclosure Material: Glass and metal inclosure Material: Glass and metal inclosure Configuration: Can input Circuit Pattern: Sin iput Design Function And Quantity: 1 amplifier, general purpose Case Outline Source And Designator: To-99 joint electron device engineering council Terminal Surface Treatment: Solder Test Data Document: Solder Test Data Document: Solder Test Data Document: Solder Test Data Document: Test Data Document: Test Data Document: Test Data Document: Solder Test Document: Solder Tes	
Between 0.165 inches and 0.185 inches Maximum Power Dissipation Rating: 400.0 milliwatis Operating Tempurature Range: 28.0/+85.0 degrees celsius Storage Tempurature Range: 28.0/+85.0 degrees celsius Storage Tempurature Range: 65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and monolithic and high gain and fixed and positive outputs Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 1 amplifier, general purpose Case Outline Source And Designator: To-99 joint electron device engineering council Terminal Surface Treatment: Solder Test Data Document: 06848-4-0032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Terminal Type And Quantity: 8 pin Shelf Life: Na Unit Of Measure: — Demilitarization: Yes - demil/mil Flig:	Body Outside Diameter:
Between 0.165 inches and 0.185 inches Maximum Power Dissipation Rating: 400.0 milliwatts  Doperating Tempurature Range: -28.0/+85.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: -Features Provided: -	Between 0.335 inches and 0.370 inches
Maximum Power Dissipation Rating: 400.0 milliwatts Operating Tempurature Range: 28.0/485.0 degrees celsius Storage Tempurature Range: 45.0/4150.0 degrees celsius Features Provided: Hermetically sealed and monolithic and high gain and fixed and positive outputs Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 1 amplifier, general purpose Case Outline Source And Designator: To-99 joint electron device engineering council Terminal Surface Treatment: 20645-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 3 pin Sheff Life: No.  Demilitarization: Yes - demili/mil Filig:	Body Height:
Operating Tempurature Range: 28.0/485.0 degrees celsius Storage Tempurature Range: 45.0/4150.0 degrees celsius Features Provided: Hermetically sealed and monolithic and high gain and fixed and positive outputs Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern:	Between 0.165 inches and 0.185 inches
Operating Tempurature Range: -28.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and monolithic and high gain and fixed and positive outputs Inclosure Material: Glass and metal Inclosure Configuration: Can Imput Circuit Pattern: Is input Circuit Pattern: Is input Orecuit Pattern: Is input Orecuit Pattern: Is maplifier, general purpose Case Outline Source And Designator: To-99 joint electron device engineering council Terminal Surface Treatment: Solder Test Data Document: 06845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: By pin Shelf Life:  Wa Unit Of Measure:	Maximum Power Dissipation Rating:
Storage Tempurature Range:  45.04-15.0 degrees celsius  Storage Tempurature Range:  45.04-15.0 degrees celsius  Features Provided: Hermetically sealed and monolithic and high gain and fixed and positive outputs Inclosure Material: Glass and metal Inclosure Configuration: Can Imput Circuit Pattern: 5 input  Design Function And Quantity: 1 amplifier, general purpose Case Outline Source And Designator: To-99 joint electron device engineering council Terminal Surface Treatment: Solider  Test Data Document: 06845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formal excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 3 pin  Shelf Life:  Wa Unit Of Measure:  — Demilitarization: Yes - demil/mli  Flig:	400.0 milliwatts
Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and monolithic and high gain and fixed and positive outputs Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 1 amplifier, general purpose Case Outline Source And Designator: T0-99 joint electron device engineering council Terminal Surface Treatment: Solder Test Data Document: De845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 8 pin Sheft Life: N/a Unit Of Measure:	Operating Tempurature Range:
Features Provided: Hermetically sealed and monolithic and high gain and fixed and positive outputs Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 1 ampliffer, general purpose Case Outline Source And Designator: To-99 joint electron device engineering council Terminal Surface Treatment: Solder Test Data Document: 106845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure:	-28.0/+85.0 degrees celsius
Features Provided: Hermetically sealed and monolithic and high gain and fixed and positive outputs Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 1 amplifier, general purpose Case Outline Source And Designator: Tro-99 joint electron device engineering council Terminal Surface Treatment: Solder Test Data Document: 106845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure:	Storage Tempurature Range:
Hermetically sealed and monolithic and high gain and fixed and positive outputs  Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 1 amplifier, general purpose Case Outline Source And Designator: T0-99 joint electron device engineering council Terminal Surface Treatment: Solder Test Data Document: D6845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "*, etc.). Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure:	-65.0/+150.0 degrees celsius
Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 1 amplifier, general purpose Case Outline Source And Designator: TO-99 joint electron device engineering council Terminal Surface Treatment: Solder Test Data Document: D6845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formal excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure:	Features Provided:
Glass and metal inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 1 amplifier, general purpose Case Outline Source And Designator: TO-99 joint electron device engineering council Terminal Surface Treatment: Solder Test Data Document: De845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: B pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Hermetically sealed and monolithic and high gain and fixed and positive outputs
Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 1 amplifier, general purpose Case Outline Source And Designator: TO-99 joint electron device engineering council Terminal Surface Treatment: Solder Test Data Document: De8845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: B pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Inclosure Material:
Input Circuit Pattern: 5 input  Design Function And Quantity: 1 amplifier, general purpose  Case Outline Source And Designator: T0-99 joint electron device engineering council  Terminal Surface Treatment: Solder  Test Data Document:  D6845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 8 pin  Shelf Life: N/a  Unit Of Measure:	Glass and metal
Input Circuit Pattern:  5 input  Design Function And Quantity:  1 amplifier, general purpose  Case Outline Source And Designator:  T0-99 joint electron device engineering council  Terminal Surface Treatment:  Solder  Test Data Document:  06845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 pin  Shelf Life:  N/a  Unit Of Measure:  ——  Demilitarization:  Yes - demil/mli  Fitg:	Inclosure Configuration:
Design Function And Quantity:  1 amplifier, general purpose Case Outline Source And Designator: T0-99 joint electron device engineering council Terminal Surface Treatment: Solder Test Data Document: 06845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure:	Can
Design Function And Quantity:  1 amplifier, general purpose  Case Outline Source And Designator:  T0-99 joint electron device engineering council  Terminal Surface Treatment:  Solder  Test Data Document:  D6845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 pin  Shelf Life:  N/a  Unit Of Measure:  —  Demilitarization:  Yes - demil/mli  Fiig:	Input Circuit Pattern:
1 amplifier, general purpose  Case Outline Source And Designator:  T0-99 joint electron device engineering council  Terminal Surface Treatment:  Solder  Test Data Document:  106845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  By pin  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  Yes - demil/mli  Flig:	5 input
Case Outline Source And Designator:  T0-99 joint electron device engineering council  Terminal Surface Treatment:  Solder  Test Data Document:  D6845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  B pin  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  Yes - demil/mli  Fiig:	Design Function And Quantity:
To-99 joint electron device engineering council  Terminal Surface Treatment:  Solder  Test Data Document:  06845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 pin  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  Yes - demil/mli  Fiig:	1 amplifier, general purpose
Terminal Surface Treatment: Solder Test Data Document:  106845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: B pin  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  Yes - demil/mli  Fiig:	Case Outline Source And Designator:
Solder  Test Data Document:  06845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 pin  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig:	T0-99 joint electron device engineering council
Test Data Document:  06845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 pin  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig:	Terminal Surface Treatment:
206845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity:  8 pin  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  Yes - demil/mli  Fiig:	Solder
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 8 pin  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	06845-4032122 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma
Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  Yes - demil/mli  Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	8 pin
Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Shelf Life:
Demilitarization: Yes - demil/mli Fiig:	N/a
Yes - demil/mli Fiig:	Unit Of Measure:
Yes - demil/mli Fiig:	
Fiig:	Demilitarization:
	Yes - demil/mli
A458a0	Fiig:
	A458a0