NSN 5962-00-372-2354

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-372-2354

| Body Length | : |
|----------------|---|
| 0.405 inches | |
| Body Width: | |
| 0.395 inches | |
| Body Height: | |
| 0.080 inches | |
| Maximum Po | wer Dissipation Rating: |
| 130.0 milliwat | ts |
| Operating Te | mpurature Range: |
| -55.0/+100.0 | degrees celsius |
| Storage Tem | purature Range: |
| -65.0/+150.0 | degrees celsius |
| Features Pro | vided: |
| Hermetically s | ealed and monolithic |
| Inclosure Ma | terial: |
| Ceramic | |
| Inclosure Co | nfiguration: |
| Flat pack | |
| Input Circuit | Pattern: |
| 6 input | |
| Terminal Sur | face Treatment: |
| Solder | |
| Voltage Ratir | ng And Type Per Characteristic: |
| 15.0 volts pov | wer source |
| Precious Mat | erial And Location: |
| Terminal surfa | ace gold |
| Precious Mat | erial: |
| Gold | |
| Test Data Do | cument: |
| 17863-711712 | 28 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any | specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Typ | e And Quantity: |
| 14 flat leads | |
| Shelf Life: | |
| N/a | |
| Unit Of Meas | ure: |
| | |
| Demilitarizat | on: |
| Yes - demil/m | li |
| Fiig: | |

A458a0