# NSN 5962-00-401-7817

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-401-7817

## **Body Length:**

Between 0.660 inches and 0.785 inches

## **Body Width:**

Between 0.220 inches and 0.280 inches

## **Body Height:**

Between 0.140 inches and 0.180 inches

## **Maximum Power Dissipation Rating:**

240.0 milliwatts

#### **Operating Tempurature Range:**

+0.0/+75.0 degrees celsius

### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

### **Features Provided:**

Monolithic and hermetically sealed and positive outputs and medium speed and w/enable and asynchronous and synchronous

#### **Inclosure Material:**

## Ceramic and glass

# Inclosure Configuration:

Dual-in-line

### **Output Logic Form:**

Diode-transistor logic

### Input Circuit Pattern:

Dual 4 input

### **Design Function And Quantity:**

2 flip-flop, j-k, clocked

### Case Outline Source And Designator:

T0-116 joint electron device engineering council

### **Terminal Surface Treatment:**

Solder

### Voltage Rating And Type Per Characteristic:

5.5 volts power source

### **Time Rating Per Chacteristic:**

100.00 nanoseconds propagation delay time, low to high level output and 55.00 nanoseconds propagation delay time, high to low level

# output

## **Terminal Type And Quantity:**

14 printed circuit

#### Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

### Fiig:

A458a0