# NSN 5962-00-402-1756

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-402-1756

#### **Body Length:**

Between 0.660 inches and 0.785 inches

#### **Body Width:**

Between 0.220 inches and 0.280 inches

#### **Body Height:**

Between 0.140 inches and 0.180 inches

#### **Maximum Power Dissipation Rating:**

177.5 milliwatts

#### **Operating Tempurature Range:**

+0.0/+75.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and medium power and medium speed

#### **Inclosure Material:**

Ceramic and glass

## Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Diode-transistor logic

#### Input Circuit Pattern:

Hex 1 input

#### **Design Function And Quantity:**

6 inverter, digital

#### Case Outline Source And Designator:

T0-116 joint electron device engineering council

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

#### Time Rating Per Chacteristic:

50.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output

#### **Test Data Document:**

54497-0141a0016 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

#### Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

# **NSN 5962-00-402-1756** Digital Microcircuit - Page 2 of 2

Fiig: A458a0

