

View Online at <https://aerobasegroup.com/nsn/5962-00-402-7810>

Body Length:

Between 0.337 inches and 0.350 inches

Body Width:

Between 0.200 inches and 0.300 inches

Body Height:

Between 0.008 inches and 0.100 inches

Maximum Power Dissipation Rating:

110.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and positive outputs and medium power and medium speed and edge triggered and presettable and w/clear

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

9 input

Design Function And Quantity:

1 flip-flop, clocked and 1 flip-flop, j-k, and input master slave

Case Outline Source And Designator:

-0-004-aa joint electron device engineering council

Time Rating Per Characteristic:

39.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

80249-911252 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0