

View Online at <https://aerobasegroup.com/nsn/5962-00-402-9337>

**Body Length:**

Between 0.250 inches and 0.260 inches

**Body Width:**

Between 0.140 inches and 0.150 inches

**Body Height:**

Between 0.035 inches and 0.050 inches

**Maximum Power Dissipation Rating:**

160.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and w/totem pole output

**Inclosure Material:**

Glass and metal

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

Quad 2 input

**Design Function And Quantity:**

4 gate, nand

**Case Outline Source And Designator:**

T0-84 joint electron device engineering council

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-1.5 volts power source and 5.5 volts power source

**Time Rating Per Characteristic:**

22.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level output

**Precious Material And Location:**

Terminals gold and body gold

**Precious Material:**

Gold

**Terminal Type And Quantity:**

14 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0