

View Online at <https://aerobasegroup.com/nsn/5962-00-406-2728>

**Body Length:**

Between 0.240 inches and 0.275 inches

**Body Width:**

Between 0.240 inches and 0.260 inches

**Body Height:**

Between 0.030 inches and 0.070 inches

**Maximum Power Dissipation Rating:**

70.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Monolithic and hermetically sealed and medium speed and medium power and positive outputs and asynchronous and edge triggered and w/enable and w/clear

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Diode-transistor logic

**Input Circuit Pattern:**

8 input

**Design Function And Quantity:**

2 flip-flop, j-k, clocked and 2 flip-flop, j-k, master slave

**Case Outline Source And Designator:**

T0-86 joint electron device engineering council

**Time Rating Per Characteristic:**

35.00 nanoseconds propagation delay time, low to high level output and 75.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output and 75.00 nanoseconds propagation delay time, high to low level output

**Precious Material And Location:**

Terminals gold

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0