

View Online at <https://aerobasegroup.com/nsn/5962-00-406-6318>

Body Length:

Between 0.240 inches and 0.290 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.030 inches and 0.070 inches

Maximum Power Dissipation Rating:

680.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+175.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and negative outputs and positive outputs and darlington-connected

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Input Circuit Pattern:

6 input

Design Function And Quantity:

1 amplifier, operational, general purpose

Case Outline Source And Designator:

T0-91 joint electron device engineering council

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

9.0 volts power source

Time Rating Per Characteristic:

280.00 nanoseconds propagation delay time, low to high level output and 280.00 nanoseconds propagation delay time, high to low level output

Special Features:

Formed leads

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Test Data Document:

42470-150171 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

10 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0