## NSN 5962-00-406-6332

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-406-6332 **Body Length:** Between 0.240 inches and 0.275 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.030 inches and 0.070 inches **Maximum Power Dissipation Rating:** 24.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and high speed and low power and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** Triple 2 input **Design Function And Quantity:** 3 receiver, line **Case Outline Source And Designator:** T0-86 joint electron device engineering council **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 1.0 volts power source **Time Rating Per Chacteristic:** 30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 14 flat leads Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

Fiig:

A458a0