NSN 5962-00-406-6338

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-406-6338

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and hybrid and burn in and w/resistor and positive outputs
Inclosure Material:
Ceramic
Inclosure Configuration:
Can
Input Circuit Pattern:
1 input
Design Function And Quantity:
1 switch, analog, single pole double throw
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
10.0 volts power source
Time Rating Per Chacteristic:
500.00 nanoseconds propagation delay time, low to high level output and 160.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96214-531895 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
10 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:
A458a0