NSN 5962-00-406-6340

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-406-6340
Body Length:
Between 0.240 inches and 0.260 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
0.185 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and medium speed and positive outputs and complementary outputs and retriggerable
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
6 input
Design Function And Quantity:
1 multivibrator, monostable
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Test Data Document:
96214-531915 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

NSN 5962-00-406-6340Digital Microcircuit - Page 2 of 2



Fiig:

A458a0