NSN 5962-00-407-7082

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-407-7082 **Body Outside Diameter:** Between 0.335 inches and 0.370 inches **Body Height:** 0.160 inches **Maximum Power Dissipation Rating:** 600.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and hybrid and positive outputs and negative outputs **Inclosure Material:** Metal **Inclosure Configuration:** Can **Input Circuit Pattern:** 3 input **Design Function And Quantity:** 1 amplifier, general purpose **Terminal Surface Treatment:** Tin **Time Rating Per Chacteristic:** 12.00 nanoseconds propagation delay time, low to high level output **Test Data Document:** 97942-649a819 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0