NSN 5962-00-410-0483

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-410-0483

Body Length:

Between 0.240 inches and 0.275 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.030 inches and 0.070 inches

Maximum Power Dissipation Rating:

30.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and hermetically sealed and positive outputs and medium speed and w/complement

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Output Logic Form:

Diode-transistor logic

Input Circuit Pattern:

3 input

Design Function And Quantity:

1 multivibrator, monostable

Case Outline Source And Designator:

T0-86 joint electron device engineering council

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Chacteristic:

40.00 nanoseconds propagation delay time, low to high level output

Test Data Document:

06424-603797 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

- --
- Demilitarization:
- Yes demil/mli

NSN 5962-00-410-0483 Digital Microcircuit - Page 2 of 2

Fiig: A458a0

