NSN 5962-00-414-7672

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/psp/5062-00-414-7672

View Online at https://aerobasegroup.com/nsn/5962-00-414-7672
Body Length:
Between 0.240 inches and 0.260 inches
Body Width:
Between 0.245 inches and 0.255 inches
Body Height:
0.065 inches
Maximum Power Dissipation Rating:
300.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and negative outputs and high speed and w/strobe
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
3 input
Design Function And Quantity:
1 comparator, voltage
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
8.0 volts power source
Time Rating Per Chacteristic:
40.00 nanoseconds propagation delay time, low to high level output
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Test Data Document:
00752-334849 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
10 flat leads
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

NSN 5962-00-414-7672 Linear Microcircuit - Page 2 of 2



Fiig:

A458a0