NSN 5962-00-414-7677

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-414-7677 **Body Outside Diameter:** Between 0.598 inches and 0.602 inches **Body Height:** 0.270 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -54.0/+125.0 degrees celsius Storage Tempurature Range: -54.0/+125.0 degrees celsius **Features Provided:** Hermetically sealed and hybrid and positive outputs and medium speed **Inclosure Material:** Glass and metal **Inclosure Configuration:** Can **Input Circuit Pattern:** Dual 2 input **Design Function And Quantity:** 2 driver, line **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source **Time Rating Per Chacteristic:** 160.00 nanoseconds propagation delay time, low to high level output and 160.00 nanoseconds propagation delay time, high to low level output **Test Data Document:**

00752-362214 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

12 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0