

View Online at <https://aerobasegroup.com/nsn/5962-00-420-5634>

Body Outside Diameter:

Between 0.335 inches and 0.370 inches

Body Height:

0.180 inches

Maximum Power Dissipation Rating:

0.5 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and edge triggered and medium speed and presettable and resettable

Inclosure Material:

Glass and metal

Inclosure Configuration:

Can

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

7 stage

Design Function And Quantity:

1 counter, binary and 1 counter, ripple

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

15.0 volts power source

Time Rating Per Characteristic:

450.00 nanoseconds propagation delay time, low to high level output

Test Data Document:

04660-77c824 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

12 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0