## NSN 5962-00-421-3105

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-421-3105

Between 0.335 inches and 0.370 inches  Body Height:  Between 0.165 inches and 0.185 inches  Maximum Power Dissipation Rating: 350.0 milliwatts  Operating Tempurature Range: +0.0/+70.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Hermetically sealed and monolithic and negative outputs and positive outputs and high gain Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input  Design Function And Quantity: 2 amplifier, radio frequency  Case Outline Source And Designator: T0-100 joint electron device engineering council  Terminal Surface Treatment: Tin  Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
Body Height: Between 0.165 inches and 0.185 inches  Maximum Power Dissipation Rating: 350.0 milliwatts  Operating Tempurature Range: +0.0/+70.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Hermetically sealed and monolithic and negative outputs and positive outputs and high gain Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 2 amplifier, radio frequency Case Outline Source And Designator: T0-100 joint electron device engineering council Terminal Surface Treatment: Tin Shelf Life: N/a Unit Of Measure: Demilitarization:	Body Outside Diameter:
Between 0.165 inches and 0.185 inches  Maximum Power Dissipation Rating: 350.0 milliwatts  Operating Tempurature Range: +0.0/+70.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Hermetically sealed and monolithic and negative outputs and positive outputs and high gain Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 2 amplifier, radio frequency Case Outline Source And Designator: T0-100 joint electron device engineering council Terminal Surface Treatment: Tin Shelf Life: N/a Unit Of Measure: Demilitarization:	Between 0.335 inches and 0.370 inches
Maximum Power Dissipation Rating: 350.0 milliwatts Operating Tempurature Range: +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and monolithic and negative outputs and positive outputs and high gain Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 2 amplifier, radio frequency Case Outline Source And Designator: T0-100 joint electron device engineering council Terminal Surface Treatment: Tin Shelf Life: N/a Unit Of Measure: Demilitarization:	Body Height:
350.0 milliwatts  Operating Tempurature Range: +0.0/+70.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Hermetically sealed and monolithic and negative outputs and positive outputs and high gain Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input  Design Function And Quantity: 2 amplifier, radio frequency  Case Outline Source And Designator: T0-100 joint electron device engineering council  Terminal Surface Treatment: Tin  Shelf Life: N/a  Unit Of Measure: Demilitarization:	Between 0.165 inches and 0.185 inches
Operating Tempurature Range: +0.0/+70.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Hermetically sealed and monolithic and negative outputs and positive outputs and high gain Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 2 amplifier, radio frequency Case Outline Source And Designator: T0-100 joint electron device engineering council Terminal Surface Treatment: Tin Shelf Life: N/a Unit Of Measure: Demilitarization:	Maximum Power Dissipation Rating:
+0.0/+70.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Hermetically sealed and monolithic and negative outputs and positive outputs and high gain Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 2 amplifier, radio frequency Case Outline Source And Designator: T0-100 joint electron device engineering council Terminal Surface Treatment: Tin Shelf Life: N/a Unit Of Measure: Demilitarization:	350.0 milliwatts
Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and monolithic and negative outputs and positive outputs and high gain Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 2 amplifier, radio frequency Case Outline Source And Designator: T0-100 joint electron device engineering council Terminal Surface Treatment: Tin Shelf Life: N/a Unit Of Measure: Demilitarization:	Operating Tempurature Range:
-65.0/+150.0 degrees celsius  Features Provided: Hermetically sealed and monolithic and negative outputs and positive outputs and high gain Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 2 amplifier, radio frequency Case Outline Source And Designator: T0-100 joint electron device engineering council Terminal Surface Treatment: Tin Shelf Life: N/a Unit Of Measure: Demilitarization:	+0.0/+70.0 degrees celsius
Features Provided: Hermetically sealed and monolithic and negative outputs and positive outputs and high gain Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 2 amplifier, radio frequency Case Outline Source And Designator: T0-100 joint electron device engineering council Terminal Surface Treatment: Tin Shelf Life: N/a Unit Of Measure: Demilitarization:	Storage Tempurature Range:
Hermetically sealed and monolithic and negative outputs and positive outputs and high gain Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 2 amplifier, radio frequency Case Outline Source And Designator: T0-100 joint electron device engineering council Terminal Surface Treatment: Tin Shelf Life: N/a Unit Of Measure: Demilitarization:	-65.0/+150.0 degrees celsius
Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 2 amplifier, radio frequency Case Outline Source And Designator: T0-100 joint electron device engineering council Terminal Surface Treatment: Tin Shelf Life: N/a Unit Of Measure: Demilitarization:	Features Provided:
Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 2 amplifier, radio frequency Case Outline Source And Designator: T0-100 joint electron device engineering council Terminal Surface Treatment: Tin Shelf Life: N/a Unit Of Measure: Demilitarization:	Hermetically sealed and monolithic and negative outputs and positive outputs and high gain
Inclosure Configuration: Can Input Circuit Pattern: 5 input Design Function And Quantity: 2 amplifier, radio frequency Case Outline Source And Designator: T0-100 joint electron device engineering council Terminal Surface Treatment: Tin Shelf Life: N/a Unit Of Measure: Demilitarization:	Inclosure Material:
Input Circuit Pattern: 5 input  Design Function And Quantity: 2 amplifier, radio frequency  Case Outline Source And Designator: T0-100 joint electron device engineering council  Terminal Surface Treatment: Tin  Shelf Life: N/a  Unit Of Measure: Demilitarization:	Glass and metal
Input Circuit Pattern: 5 input  Design Function And Quantity: 2 amplifier, radio frequency  Case Outline Source And Designator: T0-100 joint electron device engineering council  Terminal Surface Treatment: Tin  Shelf Life: N/a  Unit Of Measure:  Demilitarization:	Inclosure Configuration:
Design Function And Quantity:  2 amplifier, radio frequency  Case Outline Source And Designator:  T0-100 joint electron device engineering council  Terminal Surface Treatment:  Tin  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Can
Design Function And Quantity:  2 amplifier, radio frequency  Case Outline Source And Designator:  T0-100 joint electron device engineering council  Terminal Surface Treatment:  Tin  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Input Circuit Pattern:
2 amplifier, radio frequency  Case Outline Source And Designator:  T0-100 joint electron device engineering council  Terminal Surface Treatment:  Tin  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	5 input
Case Outline Source And Designator:  T0-100 joint electron device engineering council  Terminal Surface Treatment:  Tin  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Design Function And Quantity:
T0-100 joint electron device engineering council  Terminal Surface Treatment:  Tin  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	2 amplifier, radio frequency
Terminal Surface Treatment:  Tin  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Case Outline Source And Designator:
Tin  Shelf Life: N/a Unit Of Measure: Demilitarization:	T0-100 joint electron device engineering council
Shelf Life:  N/a Unit Of Measure: Demilitarization:	Terminal Surface Treatment:
N/a Unit Of Measure: Demilitarization:	Tin
Unit Of Measure: Demilitarization:	Shelf Life:
Demilitarization:	N/a
	Unit Of Measure:
Yes - demil/mli	Demilitarization:
	Yes - demil/mli
Fiig:	Fiig:
A458a0	A458a0