NSN 5962-00-429-5774

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-429-5774 **Body Length:** 0.796 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 420.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and dual edge triggered and negative edge triggered and w/enable and high speed and w/clear **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Dual 4 input **Design Function And Quantity:** 2 flip-flop, j-k, clocked **Case Outline Source And Designator:** D-1 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Test Data Document:** 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 14 printed circuit **Specification Data:** 81349-mil-m-38510/22 government specification Shelf Life: N/a

Demilitarization: Voc. domil/mli

Unit Of Measure:

NSN 5962-00-429-5774

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0