NSN 5962-00-433-2306

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-433-2306

View Online at https://aerobasegroup.com/nsn/5962-00-433-2306
Body Length:
Between 0.755 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Used on m12007501
Features Provided:
Hermetically sealed and monolithic and positive outputs and w/enable
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 4 input
Design Function And Quantity:
2 flip-flop, j-k, clocked
Voltage Rating And Type Per Characteristic:
5.5 volts input
Time Rating Per Chacteristic:
20.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
19200-10548615 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
1 case
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli

Fiig:

A458a0