# NSN 5962-00-433-6406

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-433-6406

## **Body Length:**

Between 1.200 inches and 1.290 inches

# Body Width:

Between 0.515 inches and 0.580 inches

# **Body Height:**

Between 0.050 inches and 0.230 inches

# **Maximum Power Dissipation Rating:**

650.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and negative outputs and positive outputs and bipolar and w/decoded output and w/enable and w/storage

and programmable and programmed

**Inclosure Material:** 

Ceramic and glass

#### Inclosure Configuration:

Dual-in-line

#### Output Logic Form:

P-type metal oxide-semiconductor logic

#### Input Circuit Pattern:

11 input

#### Case Outline Source And Designator:

-0-015-aa joint electron device engineering council

#### **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

0.3 volts power source

#### Memory Device Type:

Rom

#### **Memory Capacity:**

Unknown

#### **Test Data Document:**

92755-12793 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

#### Unit Of Measure:

# Demilitarization:

Yes - demil/mli

# NSN 5962-00-433-6406

Memory Microcircuit - Page 2 of 2

**Fiig:** A458a0

