NSN 5962-00-434-2494

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-434-2494 **Body Length:** 0.725 inches **Body Width:** 0.265 inches **Body Height:** Between 0.140 inches and 0.180 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and hybrid and negative outputs and positive outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 4 input **Design Function And Quantity:** 2 driver, line **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Time Rating Per Chacteristic:** 18.00 nanoseconds propagation delay time, low to high level output and 12.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 92755-12791 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A458a0