NSN 5962-00-434-2745

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-434-2745

Body Length:
0.670 inches
Body Width:
0.670 inches
Body Height:
0.150 inches
Maximum Power Dissipation Rating:
150.0 milliwatts
Operating Tempurature Range:
-55.0/+100.0 degrees celsius
Storage Tempurature Range:
-65.0/+125.0 degrees celsius
Features Provided:
Hybrid and adjustable and negative outputs and positive outputs and adjustable and w/enable
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
Dual 3 input
Design Function And Quantity:
2 converter, digital to analog
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
0.3 volts power source
Time Rating Per Chacteristic:
350.00 nanoseconds propagation delay time, low to high level output and 350.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Test Data Document:
13499-351-2902 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
20 flat leads
Shelf Life:
N/a
Unit Of Measure:

- --
- Demilitarization:
- Yes demil/mli

NSN 5962-00-434-2745

Linear Microcircuit - Page 2 of 2

Fiig: A458a0

