## NSN 5962-00-434-2747

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-434-2747 **Body Length:** 0.670 inches **Body Width:** 0.670 inches **Body Height:** 0.150 inches **Maximum Power Dissipation Rating:** 170.0 milliwatts **Operating Tempurature Range:** -55.0/+100.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius **Features Provided:** Hybrid and hermetically sealed and negative outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** P-type metal oxide-semiconductor logic **Input Circuit Pattern:** Quad 1 input **Design Function And Quantity:** 4 converter **Terminal Surface Treatment:** Gold **Time Rating Per Chacteristic:** 100.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold **Test Data Document:** 13499-351-2904 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 20 flat leads Shelf Life: N/a

**Demilitarization:** Yes - demil/mli

**Unit Of Measure:** 

## **NSN 5962-00-434-2747**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0